



# GROUT SEAL

## PROTECTING LAYER FOR CEMENTITIOUS GROUT

Dubond's Grout Seal is a water-based sealer that resists water and acid-based contaminants, giving a durable, stain resistant, natural-look, recommended for use on cementitious grout joints for ceramic tile installations on floors, walls and swimming pools. Equally effective for interior and exterior applications.



### Green Building Rating



Low Emission



Solvent < 5 g/kg



Low Ecological Impact



Health Care



Water Based

### Areas of Application

- Cementitious grout joints for ceramic tiles on floors, walls, swimming pools.
- Both for interior and exterior applications

### Features & Benefits

- Water based sealer
- Resists water based and acid based contaminants
- Durable
- Stain resistant
- Gives a natural & fresh look

### Method of Application

1. Grout joints must be clean dry and free of existing sealers and coating to ensure good bonding.
2. Apply 2 coats with a soft-bristle paint brush.
3. Allow a minimum of 30 minutes drying times between coats.
4. Sealed area should be kept dry for 12 hours. Achieves a full cure in 24 hours.
5. Use cotton or paper towels, Polish dry any sealer remaining on the tile and grout within 3 to 5 minutes of application.

### Precautions & Limitations :

- Do not allow sealer to come in contact with any non-recommended surface.
- Store in dry place and use in temperatures from 10° C to 30°C.

## ■ Technical Information

Appearance	<b>Liquid</b>
Colour	<b>Milky White</b>
Odor	<b>Slight, of Petroleum</b>
pH	<b>4-5</b>
Spec. Gravity	<b>Spec. Gravity (20°C): 1.01 Gr./Cc</b>
Flashing Point	<b>43°C</b>
Composition	<b>Organic resins dispersed in water.</b>

## ■ Coverage

That shall depend on the size of the grooves.

## ■ Packing

500ml, 1 Liter, 5 Liters & 20 Liters Containers.

## ■ Shelf life & storage

12-24 months in original sealed packing kept in cool and dry place.

Store in a dry place in the original container.

## ■ Health & Safety Precautions :

Keep out of reach of children. wear suitable protective clothing, gloves, and eye / face protection. after contact with skin wash immediately with plenty of clean water. in case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.

**DISCLAIMER** The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.

**Dubond Products (India) Pvt. Ltd.**  
C-3, 1001, Anushruti Tower, S.G. Highway, Thaltej,  
Ahmedabad-380054. Gujarat - INDIA  
Ph: 91-79-2685 6815 Fax: 91-79-2685 6816  
Email: [info@dubond.in](mailto:info@dubond.in) Website: [www.dubond.in](http://www.dubond.in)