



COLOURED STAIN REMOVER



STAIN CLEANER FOR COLOUR STAINS

Dubond's Coloured Stain Remover is a product for the removal of organic stains such as coffee, red wine, fruit, nicotine, colouring agents, algae, moulds etc. It can be applied on marbles, granites, stones, stoneware and other absorbent building materials. Colour Stain Remover removes the stain without damaging the surface and hardly ever leaving any holes.

Green Building Rating



Solvent < 5 g/kg



Low Ecological Impact



Health Care



Water Based

Areas of Application

- All types of floors & substrates made of
- Marbels
- Granite
- Stones
- Stoneware
- Other absorbent building materials.

Features & Benefits

- It is a product for the removal of organic stains such as coffee, red wine, fruit, nicotine, colouring agents, algae, moulds etc
- Removes the stain without damaging the surface.

Method of Application

1. Apply the pure product on the stain and let it stand from 15 minutes up to one night, depending on the nature of the stain and on the type of material.
2. Rinse well with clean water and let it dry.
3. If the stain is still visible, repeat the application.

Precautions & Limitations

- Do not use in combination with other chemical products: possible formation of dangerous gas (chlorine).
- We recommend always to test the product on an inconspicuous area, where it can not easily be seen before a general use.
- Keep the bottle closed and in a cool place. Storage stability: 6 months. Always make preliminary trials to test the stone resistance to the product.

■ Technical Information

Appearance	Transparent Liquid
Colour	Light Yellow
Odor	Typical
pH	(5% Solution) : 11- 12
Spec. Gravity	(20°C) : 1.15-1.20 Gr./Cc
Biodegradability	90%
Flashing Point	Not Flammable
Composition	Anionic and non ionic surfactants in water solution

■ Packing :

- 500 ml, 1 liter, 5 liter & 20 liter container.

■ Shelf Life & Storage :

- 6 months in original sealed packing kept in cool and dry place. store in a dry place in the original container.

■ Fortuitous leakage and waste disposal method :

- In case material is released or spilled, clean up most of the product. store the residue in plastic tank, then send to an appropriate water conditioner or call for a specialized company personnel.

DISCLAIMER The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.

Dubond Products (India) Pvt. Ltd.
C-3, 1001, Anushruti Tower, S.G. Highway, Thaltej,
Ahmedabad-380054. Gujarat - INDIA
Ph: 91-79-2685 6815 Fax: 91-79-2685 6816
Email: info@dubond.in Website: www.dubond.in